

APPLICATION

CEMENT REMOVER is used for removing cement residues from all common metal surfaces. It must not be used on zinc, aluminum, galvanized materials and stainless steel.

DIRECTIONS FOR USE

Apply *CEMENT REMOVER* with brush to surfaces to be cleaned.

- In general 2-5% dilution with water is an ideal dosage to clean Cargo Holds without affecting the Coatings.
- Use undiluted for hard cement deposits on the surfaces.
- Use diluted in solution of 1 part *CEMENT REMOVER* to 2 or 4 parts water, depending on the thickness of the cement layer.
- Rinse thoroughly with water after 10 to 15 minutes after application.

No. 5/4



Vecom Marine

clean ships - clean seas

CEMENT REMOVER

Strong acid compound specially designed for the removal of cement deposits from most common surfaces

- Fast and efficient cement removal
- Inhibited against attack on ferrous metals
- Forms protective coating on steel surfaces to which paint adheres readily
- Biodegradable and non flammable

For product characteristics and for the nature of special risks and safety advice consult our Material Safety Data Sheet.

This information is not to be taken as a warranty or representation for which we assume legal responsibility, nor as a permission, inducement or recommendation to practice any patented invention without a license. The information is offered solely for your consideration, investigation and verification.

