## SAFETY DATA SHEET



Seaclean Voyage

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Seaclean Voyage
Product code : Not available.
Product description : Not available.
Product type : Liquid.

Other means of : Not available.

identification

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

| Identified us              | ses    |
|----------------------------|--------|
| Industrial cleansing agent |        |
| Uses advised against       | Reason |
| Other than described       |        |

#### 1.3 Details of the supplier of the safety data sheet

Vecom Marine B.V. Mozartlaan 3 3144 NA Maassluis The Netherlands

Tel.: +31(0)10-5930210

e-mail address of person responsible for this SDS

: sales@vecom-marine.com

**National contact** 

#### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number**: In case of emergency please contact the Dutch National Poison Control, telephone

number: 31-(0)30-2748888. (This number is only accessible to the physician treating

the patient and only in case of accidental poisoning)

**Supplier** 

**Telephone number** : +31 10 5930210 **Hours of operation** : 09:00 - 17:00

**Information limitations**:

#### **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Date of issue/Date of revision: 1-2-2018. Page: 1/13



## **SECTION 2: Hazards identification**

Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 Carc. 2, H351 STOT RE 2, H373 Aquatic Chronic 2, H411

#### Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Carc. Cat. 3; R40

Xi; R36 R66 N; R51/53

**Human health hazards**: Limited evidence of a carcinogenic effect. Irritating to eyes. Repeated exposure

may cause skin dryness or cracking.

**Environmental hazards**: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

See Section 16 for the full text of the R phrases or H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms









Signal word : Danger

**Hazard statements**: Harmful if inhaled.

Causes skin irritation.
Causes serious eye damage.

Suspected of causing cancer.

May cause damage to organs through prolonged or repeated exposure. (blood

system, liver, lymphatic system)

Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

Prevention: Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-

ventilated area. Wash hands thoroughly after handling. Wear protective

gloves/protective clothing/eye protection/face protection.

Response : IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician. IF ON SKIN (or hair): Take off contaminated clothing and wash before reuse. Wash with plenty of soap and water. If skin irritation or rash occurs: Get

medical advice/attention.

Storage : Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Hazardous ingredients : Diesel nr.2

Isotridecanol, ethoxylated

Supplemental label

elements

: Not applicable.

**Special packaging requirements** 

Containers to be fitted

with child-resistant

fastenings

: Not applicable.

Date of issue/Date of revision: 1-2-2018. Page: 2/13

#### **SECTION 2: Hazards identification**

Tactile warning of danger: Not applicable.

2.3 Other hazards

Other hazards which do not result in classification

: Not available.

## SECTION 3: Composition/information on ingredients

Substance/mixture : Mixture

|                              |   |       | Classification  |   |         |
|------------------------------|---|-------|---|---|---------|
| Product/ingredient name      | Identifiers   | %     | 67/548/EEC  | Regulation (EC) No. 1272/2008 [CLP]   | Туре    |
| Diesel nr.2                  | CAS: 68476-30-2                                       | 75-90 | Carc. Cat. 3; R40<br>Xn; R65<br>R66<br>N; R51/53                            | Flam. Liq. 3, H226<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Carc. 2, H351<br>STOT RE 2, H373<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411 | [1]     |
| Isotridecanol, ethoxylated   | EC: 500-027-2<br>CAS: 9043-30-5                       | 7-10  | Xn; R22<br>Xi; R41  | Acute Tox. 4, H302<br>Eye Dam. 1, H318  | [1]     |
| Alcohols, C9-11, ethoxylated | CAS: 68439-46-3                                       | 1-3   | Xn; R22<br>Xi; R41  | Acute Tox. 4, H302<br>Eye Dam. 1, H318  | [1]     |
| 2-butoxyethanol              | EC: 203-905-0<br>CAS: 111-76-2<br>Index: 603-014-00-0 | 1-3   | Xn; R20/21/22<br>Xi; R36/38   | Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319   | [1] [2] |
|                              |   |       | See Section 16 for<br>the full text of the R-<br>phrases declared<br>above. | See Section 16 for the full text of the H statements declared above.  |         |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General

: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

Eye contact

: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact

Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Date of issue/Date of revision: 1-2-2018. Page: 3/13



#### SECTION 4: First aid measures

#### Ingestion

If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

#### **Protection of first-aiders**

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

Specific treatments

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

: No specific treatment.

See toxicological information (Section 11)

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media

: Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.

Unsuitable extinguishing media

: Do not use water jet.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters

: Appropriate breathing apparatus may be required.

Date of issue/Date of revision: 1-2-2018. Page: 4/13



#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### 6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

#### 6.3 Methods and materials for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Preferably clean with a detergent. Avoid using solvents.

#### 6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

: Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

To dissipate static electricity during transfer, earth drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws. Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

#### 7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### 7.3 Specific end use(s)

Recommendations : Not available.

Date of issue/Date of revision: 1-2-2018.

## **SECTION 7: Handling and storage**

Industrial sector specific solutions

: Not available.

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 8.1 Control parameters

#### **Occupational exposure limits**

| Product/ingredient name | Exposure limit values  |  |
|-------------------------|--|--|
|                         | EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values STEL: 246 mg/m³ 15 minute(s). STEL: 50 ppm 15 minute(s). TWA: 98 mg/m³ 8 hour(s). TWA: 20 ppm 8 hour(s). |  |

## Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

#### **Derived effect levels**

No DELs available.

#### **Predicted effect concentrations**

No PECs available.

#### 8.2 Exposure controls

Appropriate engineering controls

: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

#### Individual protection measures

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## Eye/face protection Skin protection

: Wear safety glasses with side protection in accordance with EN 166.

**Hand protection** 

: Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Gloves

: Wear suitable gloves tested to EN374. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances. Nitrile gloves.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Date of issue/Date of revision: 1-2-2018. Page: 6/13

## **SECTION 8: Exposure controls/personal protection**

**Body protection** 

Personnel should wear antistatic clothing made of natural fibres or of hightemperature-resistant synthetic fibres.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

If workers are exposed to concentrations above the exposure limit, they must use

appropriate, certified respirators.

**Environmental exposure** 

controls

: Do not allow to enter drains or watercourses.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state : Liquid.

Colour : Yellow. [Light] **Odour** : Characteristic. Not available. Odour threshold pН : Not applicable. : Not available. Melting point/freezing point : Not available. Initial boiling point and boiling

range

: Closed cup: >65°C Flash point

: Not available. **Evaporation rate** : Not available. Flammability (solid, gas) **Burning time** : Not applicable. : Not applicable. **Burning rate** 

Upper/lower flammability or

explosive limits

: Not available.

Vapour pressure : Not available. : Not available. Vapour density : 0.84 to 0.86 Relative density : Not available. Solubility(ies) : Not available.

Partition coefficient: n-

octanol/water

**Auto-ignition temperature** : Not available. **Decomposition temperature** : Not available. : Not available. **Viscosity Explosive properties** : Not available.

**Oxidising properties** : Not available.

#### 9.2 Other information

No additional information.

Date of issue/Date of revision : 1-2-2018.

## **SECTION 10: Stability and reactivity**

10.1 Reactivity : No speci

: No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition

products.

**10.5 Incompatible materials**: Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

There are no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### **Acute toxicity**

| Product/ingredient name      | Result                          | Species | Dose        | Exposure |
|------------------------------|---------------------------------|---------|-------------|----------|
| Diesel nr.2                  | LC50 Inhalation Dusts and mists | Rat     | 1 to 5 mg/l | 4 hours  |
|                              | LD50 Dermal                     | Rabbit  | >2000 mg/kg | -        |
|                              | LD50 Oral                       | Rat     | >5000 mg/kg | -        |
| Alcohols, C9-11, ethoxylated | LD50 Oral                       | Rat     | 1378 mg/kg  | -        |
| 2-butoxyethanol              | LD50 Oral                       | Rat     | 470 mg/kg   | -        |

**Conclusion/Summary**: Not available.

#### **Acute toxicity estimates**

| Route                        | ATE value     |
|------------------------------|---------------|
| Oral                         | 5130,9 mg/kg  |
| Dermal                       | 69620,3 mg/kg |
| Inhalation (vapours)         | 696,2 mg/l    |
| Inhalation (dusts and mists) | 1,764 mg/l    |

**Irritation/Corrosion** 

Conclusion/Summary : Not available.

**Sensitisation** 

**Conclusion/Summary**: Not available.

Date of issue/Date of revision: 1-2-2018. Page: 8/13



## **SECTION 11: Toxicological information**

**Mutagenicity** 

**Conclusion/Summary**: Not available.

**Carcinogenicity** 

**Conclusion/Summary**: Not available.

**Reproductive toxicity** 

**Conclusion/Summary**: Not available.

**Teratogenicity** 

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

|             | Product/ingredient name | Category   | Route of exposure | Target organs                                  |
|-------------|-------------------------|------------|-------------------|--|
| Diesel nr.2 |                         | Category 2 | Not determined    | blood system, liver<br>and lymphatic<br>system |

#### **Aspiration hazard**

| Product/ingredient name | Result                         |  |
|-------------------------|--------------------------------|--|
| Diesel nr.2             | ASPIRATION HAZARD - Category 1 |  |

Other information : Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

There are no data available on the preparation itself.

Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 3 and 15 for details.

| Product/ingredient name      | Result   | Species   | Exposure             |
|------------------------------|--|---|----------------------|
| Alcohols, C9-11, ethoxylated | Acute EC50 5,36 mg/L Fresh water   | Crustaceans - Ceriodaphnia<br>dubia - Neonate - <24 hours                   | 48 hours             |
|                              | Acute EC50 2686 ug/L Fresh water   | Daphnia - Daphnia magna -<br>Neonate - <24 hours                            | 48 hours             |
|                              | Acute LC50 8500 ug/L Fresh water   | Fish - Pimephales promelas  | 96 hours             |
| 2-butoxyethanol              | Acute EC50 >1000 mg/L Fresh water  | Daphnia - Daphnia magna - <24 hours   | 48 hours             |
|                              | Acute LC50 800000 ug/L Marine water<br>Acute LC50 1250000 ug/L Marine<br>water | Crustaceans - Crangon crangon<br>Fish - Menidia beryllina - 40 to<br>100 mm | 48 hours<br>96 hours |

**Conclusion/Summary**: Not available.

#### 12.2 Persistence and degradability

**Conclusion/Summary**: Not available.

#### 12.3 Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| Seaclean Voyage         |        | -   | low       |

Date of issue/Date of revision: 1-2-2018. Page: 9/13



## **SECTION 12: Ecological information**

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

#### 12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

**12.6 Other adverse effects**: No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

**Hazardous waste** 

**Packaging** 

**Methods of disposal** 

- : The classification of the product may meet the criteria for a hazardous waste.
- : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** 

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

|                                    | ADR/RID   | ADN/ADNR  | IMDG  | IATA   |
|------------------------------------|---|---|---|--|
| 14.1 UN number                     | UN3082  | UN3082  | UN3082  | UN3082   |
| 14.2 UN proper shipping name       | ENVIRONMENTALLY<br>HAZARDOUS<br>SUBSTANCE,<br>LIQUID, N.O.S.<br>(Diesel nr.2) | ENVIRONMENTALLY<br>HAZARDOUS<br>SUBSTANCE,<br>LIQUID, N.O.S.<br>(Diesel nr.2) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diesel nr.2). Marine pollutant (Diesel nr.2) | Environmentally<br>hazardous substance,<br>liquid, n.o.s. (Diesel<br>nr.2) |
| 14.3 Transport<br>hazard class(es) | 9   | 9   | 9   | 9  |
| 14.4 Packing group                 | III   | III   | III   | III  |

Date of issue/Date of revision: 1-2-2018. Page: 10/13

| Seaclean Voyage                   |  |  |  |  |
|-----------------------------------|--|--|--|--|
| SECTION 14:                       | Transport inform   | ation  |  |  |
| 14.5<br>Environmental<br>hazards  | Yes.   | Yes.   | Yes.   | Yes.   |
| 14.6 Special precautions for user | Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. | Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. | Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. | Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. |
| Additional information            | Hazard identification number 90  Limited quantity 5 L  Special provisions 274, 335, 601  Tunnel code (E)   | -  | Emergency<br>schedules (EmS)<br>F-A, S-F   | Passenger and Cargo Aircraft Quantity limitation: 450 L Packaging instructions: 964 Cargo Aircraft Only Quantity limitation: 450 L Packaging instructions: 964 Limited Quantities - Passenger Aircraft     |

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not available.

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

**Other EU regulations** 

**VOC for Ready-for-Use** : Not applicable.

**Mixture** 

**Europe inventory**: Not determined.

Black List Chemicals : Not listed

Date of issue/Date of revision : 1-2-2018. Page: 11/13

Quantity limitation:

30 kg Packaging instructions: Y964

## **SECTION 15: Regulatory information**

Priority List Chemicals
Integrated pollution
prevention and control

list (IPPC) - Air

: Not listed: Not listed

Integrated pollution prevention and control list (IPPC) - Water

: Not listed

| Product/ingredient name | Carcinogenic effects | Mutagenic effects | Developmental effects | Fertility effects |
|-------------------------|----------------------|-------------------|-----------------------|-------------------|
| Diesel nr.2             | Carc. 2, H351        | -                 | -                     | -                 |

**Industrial use** 

: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

#### **International regulations**

**Chemical Weapons** 

Convention List Schedule I

**Chemicals** 

: Not listed

Chemical Weapons
Convention List Schedule II

Convention List Sc

**Chemicals** 

: Not listed

**Chemical Weapons** 

**Convention List Schedule III** 

**Chemicals** 

: Not listed

15.2 Chemical Safety

**Assessment** 

: Complete.

#### **SECTION 16: Other information**

CEPE code : 1

Indicates information that has changed from previously issued version.

**Abbreviations and** 

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification          | Justification      |
|-------------------------|--------------------|
| Acute Tox. 4, H332      | Calculation method |
| Skin Irrit. 2, H315     | Calculation method |
| Eye Dam. 1, H318        | Calculation method |
| Carc. 2, H351           | Calculation method |
| STOT RE 2, H373         | Calculation method |
| Aquatic Chronic 2, H411 | Calculation method |

Date of issue/Date of revision : 1-2-2018. Page: 12/13

#### **SECTION 16: Other information**

Full text of abbreviated H statements

: H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

Harmful in contact with skin. H312 H315 Causes skin irritation.

H318 Causes serious eye damage. Causes serious eye irritation. H319

H332 Harmful if inhaled.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

ACUTE TOXICITY: ORAL - Category 4 : Acute Tox. 4, H302 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4

Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4 Aquatic Chronic 2, H411 AQUATIC TOXICITY (CHRONIC) - Category 2

Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1 **CARCINOGENICITY - Category 2** Carc. 2, H351

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Dam. 1, H318 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2

Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3

SKIN CORROSION/IRRITATION - Category 2 Skin Irrit. 2, H315 **STOT RE 2, H373** SPECIFIC TARGET ORGAN TOXICITY (REPEATED

EXPOSURE) [blood system, liver and lymphatic system] -

Category 2

Full text of abbreviated R

phrases

: R40- Limited evidence of a carcinogenic effect.

R22- Harmful if swallowed.

R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.

R65- Harmful: may cause lung damage if swallowed.

R41- Risk of serious damage to eyes.

R36- Irritating to eyes.

R36/38- Irritating to eyes and skin.

R66- Repeated exposure may cause skin dryness or cracking.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

**Full text of classifications** 

[DSD/DPD]

: Carc. Cat. 3 - Carcinogen category 3

Xn - Harmful Xi - Irritant

N - Dangerous for the environment

**Date of printing** Date of issue/ Date of

revision

Version

: 1-2-2018. : 1-2-2018.

1.01

: 3-1-2018. Date of previous issue

**Notice to reader** 

This material safety data sheet contains information about the properties and safety risks of the product it describes, as known on the date of issue. It does not constitute a guarantee of any property or quality of the product. The information is intended exclusively as a guide to safely operating, storing and transporting the product and what do if it is released.

The information concerns the product itself and does not apply to any application or use of it, whether or not in combination with any other product or in any process. Responsibility for assessing the related implications and risks rests entirely with the user. This material safety data sheet has been compiled with the greatest possible care but is based in part on information in the public domain. For this reason Vecom is unable to accept any liability for the accuracy or completeness of the information.

Date of issue/Date of revision : 1-2-2018.