SAFETY DATA SHEET



Uriclean Concentrate

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Uriclean Concentrate : 003.010000000314 **Product code Product description** : Not available. **Product type** : Liquid.

Other means of

: Not available.

identification

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses					
Industrial cleansing agent					
Uses advised against	Reason				

1.3 Details of the supplier of the safety data sheet

VECOM

C/O: Westchem BV. Mozartlaan 3

NL-3144 NA Maassluis

The Netherlands

Tel.: +31(0)10-5930299 Fax: +31(0)10-5930225

e-mail address of person

responsible for this SDS

: msds@vecom.nl

National contact

1.4 Emergency telephone number

National advisory body/Poison Centre

: In case of emergency please contact the Dutch National Poison Control, telephone **Telephone number**

number: 31-(0)30-2748888. (This number is only accessible to the physician treating

the patient and only in case of accidental poisoning)

Supplier

Telephone number : +31 10 5930299 **Hours of operation** : Hours of operation 08:30 - 17:00 08:30 - 17:00

Information limitations

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Corr. 1A, H314 Eye Dam. 1, H318

Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : C; R34

Date of issue/Date of revision : 16-7-2015. Page: 1/12

SECTION 2: Hazards identification

: Causes burns. **Human health hazards**

See Section 16 for the full text of the R phrases or H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word : Danger

Hazard statements : Causes severe skin burns and eye damage.

Precautionary statements

Prevention : Wear protective gloves. Wear eye or face protection. Wear protective clothing.

: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for **Response**

breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower. Immediately call a POISON CENTER or physician. IF IN EYES:

Immediately call a POISON CENTER or physician.

Storage : Store locked up. **Disposal** : Not applicable. : phosphoric acid **Hazardous ingredients** hydrogen chloride

2-butoxyethanol

Isotridecanol, ethoxylated

Supplemental label

elements

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Other hazards which do not : Not available.

result in classification

SECTION 3: Composition/information on ingredients

Substance/mixture : Mixture

			Classification		
Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре
phosphoric acid	EC: 231-633-2 CAS: 7664-38-2 Index: 015-011-00-6	5-10	C; R34	Met. Corr. 1, H290 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318	[1] [2]
hydrogen chloride	EC: 231-595-7 CAS: 7647-01-0 Index: 017-002-00-2	1-5	C; R34, R35	Press. Gas, H280 Acute Tox. 3, H331 Skin Corr. 1A, H314 Eye Irrit. 2, H319	[1] [2]
2-butoxyethanol	EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	1-3	Xn; R20/21/22 Xi; R36/38	Eye Irrit. 2, H319	[1] [2]
Isotridecanol, ethoxylated	EC: 500-027-2 CAS: 9043-30-5	1-3	Xn; R22 Xi; R41	Acute Tox. 4, H302 Eye Dam. 1, H318	[1]

Date of issue/Date of revision : 16-7-2015. Page: 2/12

Uriclean Concentrate								
SECTION 3: Composition/information on ingredients								
	See Section 16 for the full text of the R- phrases declared above.	See Section 16 for the full text of the H statements declared above.						

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General : I

: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

Eye contact

: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion

: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

See toxicological information (Section 11)

Date of issue/Date of revision : 16-7-2015. Page: 3/12

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Recommended: alcohol-resistant foam, CO₂, powders, water spray.

Unsuitable extinguishing media

: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters

: Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and materials for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

: Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

To dissipate static electricity during transfer, earth drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel.

Date of issue/Date of revision : 16-7-2015. Page: 4/12

SECTION 7: Handling and storage

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

Recommendations **Industrial sector specific** : Not available. solutions

: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
phosphoric acid	EU OEL (Europe, 12/2009). Notes: list of indicative occupational exposure limit values
	STEL: 2 mg/m³, 0 times per shift, 15 minute(s). TWA: 1 mg/m³, 0 times per shift, 8 hour(s).
hydrogen chloride	EU OEL (Europe, 12/2009). Notes: list of indicative occupational
	exposure limit values TWA: 5 ppm 8 hour(s). TWA: 8 mg/m³ 8 hour(s). STEL: 10 ppm 15 minute(s). STEL: 15 mg/m³ 15 minute(s).
2-butoxyethanol	EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values STEL: 246 mg/m³ 15 minute(s). STEL: 50 ppm 15 minute(s). TWA: 98 mg/m³ 8 hour(s). TWA: 20 ppm 8 hour(s).

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Derived effect levels

No DELs available.

Predicted effect concentrations

No PECs available.

8.2 Exposure controls

Date of issue/Date of revision : 16-7-2015. Page: 5/12



SECTION 8: Exposure controls/personal protection

Appropriate engineering controls

: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Individual protection measures

: Wash hands, forearms and face thoroughly after handling chemical products, before Hygiene measures

eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Eye/face protection

Skin protection

: Use safety eyewear designed to protect against splash of liquids.

Hand protection : Barrier creams may help to protect the exposed areas of the skin but should not be

applied once exposure has occurred.

: Personnel should wear antistatic clothing made of natural fibres or of high-**Body protection**

temperature-resistant synthetic fibres.

: Appropriate footwear and any additional skin protection measures should be selected Other skin protection

based on the task being performed and the risks involved and should be approved by

a specialist before handling this product.

If workers are exposed to concentrations above the exposure limit, they must use Respiratory protection

appropriate, certified respirators.

Environmental exposure

controls

: Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Colour Not available. **Odour** Characteristic. : Not available. **Odour threshold**

pН : 2

Melting point/freezing point : Not available.

Initial boiling point and boiling

range

: 100°C

Flash point : Closed cup: Not applicable. [Product does not sustain combustion.]

Evaporation rate Not available. Flammability (solid, gas) Not available. **Burning time** : Not applicable. **Burning rate** : Not applicable. : Not available. Upper/lower flammability or

explosive limits

Vapour pressure : 2,3 kPa [20°C] : Not available. Vapour density : Not available. Relative density

Solubility(ies) Easily soluble in the following materials: cold water and hot water.

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature : Not applicable. **Decomposition temperature** Not available. **Viscosity** : Not available. **Explosive properties** Not available. Oxidising properties : Not available.

Date of issue/Date of revision : 16-7-2015. Page: 6/12

SECTION 9: Physical and chemical properties

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

: Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

10.3 Possibility of hazardous: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

: When exposed to high temperatures may produce hazardous decomposition products.

10.5 Incompatible materials

: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
	LD50 Oral LC50 Inhalation Vapour LD50 Dermal LD50 Oral		1,25 g/kg 2 to 20 mg/l 2270 mg/kg 6600 mg/kg	- 4 hours -

Conclusion/Summary

: Not available.

Acute toxicity estimates

Route	ATE value	
Oral Inhalation (vapours)	11291,8 mg/kg 65,88 mg/l	

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation

Date of issue/Date of revision : 16-7-2015. Page: 7/12

SECTION 11: Toxicological information

hydrogen chloride	Eyes - Mild irritant	Rabbit	-	0,5 minutes 5	-
				milligrams	
	Skin - Mild irritant	Human	-	24 hours 4	-
				Percent	
2-butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
_	-			milligrams	
	Eyes - Severe irritant	Rabbit	-	100	-
				milligrams	
	Skin - Mild irritant	Rabbit	-	500	-
				milligrams	

Conclusion/Summary

: Not available.

Sensitisation

Conclusion/Summary: Not available.

Mutagenicity

Conclusion/Summary: Not available.

Carcinogenicity

Conclusion/Summary: Not available.

Reproductive toxicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the preparation itself.

Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

Product/ingredient name	Result	Species	Exposure
phosphoric acid	Acute EC50 105 ppm Fresh water	Daphnia - Daphnia magna - <24 hours	48 hours
	Acute LC50 60 ppm Fresh water	Fish - Lepomis macrochirus - 0,39 g	96 hours
hydrogen chloride	Acute LC50 240000 ug/L Marine water	Crustaceans - Carcinus maenas - Adult	48 hours
	Acute LC50 282 ppm Fresh water	Fish - Gambusia affinis - Adult	96 hours
2-butoxyethanol	Acute EC50 >1000 mg/L Fresh water	Daphnia - Daphnia magna - <24 hours	48 hours
	Acute LC50 800000 ug/L Marine water Acute LC50 1250000 ug/L Marine water	Crustaceans - Crangon crangon Fish - Menidia beryllina - 40 to 100 mm	48 hours 96 hours

Conclusion/Summary: Not available.

12.2 Persistence and degradability

Conclusion/Summary: Not available.

Date of issue/Date of revision : 16-7-2015. Page: 8/12

SECTION 12: Ecological information

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Uriclean Concentrate		-	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Hazardous waste

Packaging

Methods of disposal

: The classification of the product may meet the criteria for a hazardous waste.

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN/ADNR	IMDG	IATA
14.1 UN number	UN1789	UN1789	UN1789	UN1789
14.2 UN proper shipping name	HYDROCHLORIC ACID	HYDROCHLORIC ACID	HYDROCHLORIC ACID	Hydrochloric acid
14.3 Transport hazard class(es)	8	8	8	8
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	No.	No.	No.	No.

Date of issue/Date of revision : 16-7-2015. Page: 9/12

SECTION 14: Transport information

· · · · · · · · · · · · · · · · · · ·	<u> </u>	I —	1	<u> </u>
14.6 Special precautions for user	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Additional information	Hazard identification number 80 Limited quantity 1 L Special provisions 520 Tunnel code (E)	-	Emergency schedules (EmS) F-A, S-B	Passenger and Cargo Aircraft Quantity Ilimitation: 1 L Packaging instructions: 851 Cargo Aircraft Only Quantity limitation: 30 L Packaging instructions: 855 Limited Quantities - Passenger Aircraft Quantity limitation: 0.5 L Packaging instructions: Y840

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

VOC for Ready-for-Use

Mixture

: Not applicable.

: Not applicable.

: All components are listed or exempted. **Europe inventory**

Black List Chemicals : Not listed : Not listed **Priority List Chemicals** Integrated pollution : Not listed

(IPPC) - Air

Integrated pollution

prevention and control list

prevention and control list (IPPC) - Water

: Not listed

Date of issue/Date of revision : 16-7-2015. Page: 10/12



SECTION 15: Regulatory information

Industrial use

: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

International regulations

Chemical Weapons

Convention List Schedule I

Chemicals

: Not listed

Chemical Weapons

Convention List Schedule II

Chemicals

: Not listed

Chemical Weapons Convention List Schedule III

Chemicals

: Not listed

15.2 Chemical Safety

Assessment

: Not yet complete.

SECTION 16: Other information

CEPE code

Indicates information that has changed from previously issued version.

Abbreviations and acronyms: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Corr. 1A, H314	On basis of test data
Eye Dam. 1, H318	On basis of test data

Full text of abbreviated H

statements

: H280 Contains gas under pressure; may explode if heated.

H290 May be corrosive to metals.

H302 Harmful if swallowed.

Causes severe skin burns and eye damage. H314

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H331 Toxic if inhaled.

Full text of classifications [CLP/GHS]

: Acute Tox. 3, H331 **ACUTE TOXICITY: INHALATION - Category 3**

Acute Tox. 4, H302 **ACUTE TOXICITY: ORAL - Category 4**

Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2

CORROSIVE TO METALS - Category 1 Met. Corr. 1, H290

Press. Gas Comp. Gas, GASES UNDER PRESSURE - Compressed gas

H280

Skin Corr. 1A, H314 SKIN CORROSION/IRRITATION - Category 1A Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B

Full text of abbreviated R

phrases

: R22- Harmful if swallowed.

R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.

R34- Causes burns. R35- Causes severe burns.

R41- Risk of serious damage to eyes. R36/38- Irritating to eyes and skin.

Full text of classifications

[DSD/DPD]

: C - Corrosive Xn - Harmful Xi - Irritant

Date of issue/Date of revision : 16-7-2015. Page: 11/12

SECTION 16: Other information

Date of printing : 16-7-2015.

Date of issue/ Date of : 16-7-2015.

revision

Date of previous issue : No previous validation.

Version : 1

Notice to reader

This material safety data sheet contains information about the properties and safety risks of the product it describes, as known on the date of issue. It does not constitute a guarantee of any property or quality of the product. The information is intended exclusively as a guide to safely operating, storing and transporting the product and what do if it is released.

The information concerns the product itself and does not apply to any application or use of it, whether or not in combination with any other product or in any process. Responsibility for assessing the related implications and risks rests entirely with the user. This material safety data sheet has been compiled with the greatest possible care but is based in part on information in the public domain. For this reason Vecom is unable to accept any liability for the accuracy or completeness of the information.

Date of issue/Date of revision : 16-7-2015. Page: 12/12

